LUMI AUDIO
LUMIAUDIO.CN

**CMB Series**

# COMMERCIAL MULTI-INPUT MIXING AMPLIFIER

The perfect amplifier for large commercial audio applications
where the mixing of multiple input sources is required.
Voice-over music paging from multiple sources
including digital media, line inputs, and multiple mic inputs.

# CMB Series | Affordable, versatile, and built to last.

- Independent volume control of up to 6 speaker "zones"
- 7 inputs including RCA Line Inputs, Mics, and USB/SD digital media player

| | |
|---|---|
| Total Harmonic Distortion | 60Hz – 16kHz<0.1 % |
| Signal-to-Noise Ratio | MIC: 66dB, LINE: 102dB |
| Input | MIC IN x 2, LINE IN x 3, USB/ SD/Bluetooth/FM |
| Input Impedance | MIC:600 ohm, LINE 10k ohm |
| Input Sensitivity | MIC: 66dB, LINE: -10dB |
| Output | 8ohm, 70, 100 V |
| Additional Outputs | 6 speaker "zones", monitor out/ bridge out x 1 |
| Frequency Response (±3dB) | 60Hz - 16kHz ±0.5dB |

## CMB-120

Output Power (Rated): 120W
Product Weight: 6.7kg(14.8lbs)
Product Dimension(mm):
480x355x98(18.9"x14"x3.9")

## CMB-180

Output Power (Rated):180W
Product Weight: 8.1kg(17.9lbs)
Product Dimension(mm):
480x380x98(18.9"x15"x3.9")

## CMB-240

Output Power (Rated):240W
Product Weight: 9.6kg(21.2lbs)
Product Dimension(mm):
480x380x98(18.9"x15"x3.9")

Ningbo Lumiaudio Electronic Technology Ltd.
belongs to LUMI LEGEND GROUP

Add: 22/F., Building 1, Lisi Plaza,Huifeng East Road,
Ningbo, China 315100

Tel: 86-574-27956565
Fax: 86-574-27956599

E-mail: info@lumiaudio.cn
Website: www.lumiaudio.cn